



Our Fraste PL G rubber tracked drill is ideal for Geotechnical and Hydro Geological projects. With its companion 200 PSI/ 300 CFM air compressor and high pressure water/fluid pumps this drill is capable of coring, air rotary, mud rotary and auger drilling. Removeable ice cleats are installed for winter trail conditions.

## Fraste PL G



**UNIT# DR607**

### Factory Drilling Capacities and Methods:

- Diamond core drilling ~100 M (HQ)
- Rotary drilling ~50 M Casing / 150 M OH
- Hollow Stem Auger
- Continuous Flight Auger

Note: Above drilling capacities may vary according to subsurface conditions

### Drill Specifications:

- 75 HP Diesel powered with Pro Heat
- Environ Hydraulic fluid
- 18 ft mast with pump, 8 ft of stroke feed
- 600 RPM head, 3500 ft lbs torque
- 10, 000 lbs pulback force
- Three winch lines capable of hanging 45 ft of rods during SPT sampling
- Casing/Rod Clamp with hydraulic rod break
- Efficiency calibrated automatic SPT hammer
- Moyno 400 PSI grout pump
- FMC Bean 4 Cyl. 1000 PSI coring pump
- Remote rupe/centerline 100/300 gal. mud pump
- Remote air compressor on service unit
- Hypro 500 PSI water injection pump for air rotary
- On board toolboxes and misc. tooling
- Quick set up rod racks and engineer tent

**For more information, please call: 1 855-WT DRILL**